



# PDS

## PERMANGANATE DOSING SYSTEM

cod. 20211280



EMEC S.r.l. Via Donatori di Sangue, 1 - 02100 Rieti - Italia  
T. +39 0746 2284 1 F. +39 0746 2284 2  
info@emecpumps.com - www.emecpumps.com

# PDS

## PERMANGANATE DOSING SYSTEM

PDS (Permanganate Dosing System) is a compact, fully automatic system designed for the preparation and continuous dosing of **Sodium Permanganate (NaMnO<sub>4</sub>)** and **Potassium Permanganate (KMnO<sub>4</sub>)** solutions, starting from **liquid solutions**, in drinking water or for industrial applications.

It is intended for applications where **reliability**, **dosing accuracy**, and **operational continuity** are required. The system allows **flow-proportional control** and automatic management of the oxidizing agent via a touchscreen panel.

The system can be integrated with **PermaTest**, a solution for continuous residual analysis, ensuring complete control of the oxidation process.

## APPLICATION FIELDS




## MAIN FEATURES

- Permanganate dosing setpoint in mg/L
- Automatic flow-proportional dosing
- Automatic calibration of dosing pumps
- Manual mode with preset flow rate
- Flow-proportional control via 4-20 mA signal
- PID control with integrated flow meter
- PID control of dosing pumps
- Flow monitoring and process alarms

## AVAILABLE CONFIGURATIONS

### POTASSIUM PERMANGANATE




#### WHERE

- ✓ Removal of iron and manganese
- ✓ Oxidation of hydrogen sulfide (H<sub>2</sub>S)
- ✓ Odor control and organic compound oxidation
- ✓ Pre-oxidation in drinking water treatment

#### WHY

- ✓ High chemical stability of the solution
- ✓ Lower aggressiveness toward certain materials
- ✓ Good long-term storage stability
- ✓ Lower maximum concentration in solution

### SODIUM PERMANGANATE



#### WHERE

- ✓ Industrial water treatment
- ✓ Environmental remediation and contaminated soil treatment
- ✓ Oxidation of complex organic compounds
- ✓ Systems with continuous and controlled dosing

#### WHY

- ✓ Much higher solubility
- ✓ Higher operating concentrations
- ✓ Greater fluidity and ease of pumping
- ✓ Higher oxidizing reactivity
- ✓ Particularly suitable for continuous systems

## TECHNICAL SPECIFICATIONS

Power supply 230 Vac ±10% - 50/60 Hz

Power consumption Approx. 100 W

Protection rating IP65 / NEMA 4

HMI display 7" touchscreen

Inputs

- 4-20 mA analog signal (flow rate)
- Remote Start/Stop
- Level alarm

Operating temperature 0 ÷ 40 °C

## SYSTEM COMPONENTS

